


RS1G126 Single Bus Buffer Gate With 3-State Output

1 FEATURES

- **Operating Voltage Range: 1.65V to 5.5V**
- **Low Power Consumption: 1 μ A (Max)**
- **Operating Temperature Range: -40°C to 125°C**
- **Inputs Accept Voltage to 5.5V**
- **\pm 24mA Output Drive at $V_{CC}=3.0V$**
- **Latch-up Performance Exceeds 100mA**
- **Micro Size Packages: SOT23-5, SC70-5, XDFN1X1-6**

2 APPLICATIONS

- **AV Receiver**
- **Cable Modem Termination Systems**
- **Digital Picture Frame (DPF)**
- **High-Speed Data Acquisition and Generation**
- **Motor Controls: High-Voltage**
- **Personal Navigation Device (GPS)**
- **Portable Media Player**
- **Video Communication Systems**



3 DESCRIPTIONS

The single buffer is designed for 1.65V to 5.5V V_{CC} operation. The RS1G126 device is single line driver with 3-state output. The output is disabled when the output-enable input is low.

This device is fully specified for partial-power-down applications using I_{off} . The I_{off} circuitry disables the outputs, preventing damaging current backflow through the device when it is powered down.

To ensure the high-impedance state during power up or power down, OE should be tied to GND through a pulldown resistor, the minimum value of the resistor is determined by the current-sourcing capability of the driver.

The RS1G126 is available in Green SOT23-5, SC70-5 and XDFN1X1-6 packages. It operates over an ambient temperature range of -40°C to 125°C.

Device Information ⁽¹⁾

| PART NUMBER | PACKAGE | BODY SIZE (NOM) |
|-------------|-----------|------------------------|
| RS1G126 | SOT23-5 | 2.92mm \times 1.60mm |
| | SC70-5 | 2.10mm \times 1.25mm |
| | XDFN1X1-6 | 1.00mm \times 1.00mm |

(1) For all available packages, see the orderable addendum at the end of the data sheet.

4 FUNCTION TABLE

| INPUTS | | OUTPUT |
|--------|---|--------|
| OE | A | Y |
| H | H | H |
| H | L | L |
| L | X | Z |

H=HIGH Logic Level
 L=LOW Logic Level
 X=Don't Care
 Z=High-impedance OFF-state

Table of Contents

| | |
|---|----|
| 1 FEATURES | 1 |
| 2 APPLICATIONS | 1 |
| 3 DESCRIPTIONS | 1 |
| 4 FUNCTION TABLE | 1 |
| 5 REVISION HISTORY | 3 |
| 6 PACKAGE/ORDERING INFORMATION ⁽¹⁾ | 4 |
| 7 PIN CONFIGURATIONS | 5 |
| 8 SPECIFICATIONS | 6 |
| 8.1 Absolute Maximum Ratings | 6 |
| 8.2 ESD Ratings | 6 |
| 9 ELECTRICAL CHARACTERISTICS | 7 |
| 9.1 Recommended Operating Conditions | 7 |
| 9.2 DC Characteristics | 8 |
| 9.3 Switching Characteristics, C _L =15pF | 9 |
| 9.4 Switching Characteristics, C _L =30pF or 50pF | 9 |
| 9.5 Operating Characteristics | 9 |
| 10 PARAMETER MEASUREMENT INFORMATION | 10 |
| 11 PACKAGE OUTLINE DIMENSIONS | 11 |
| 12 TAPE AND REEL INFORMATION | 14 |

5 REVISION HISTORY

Note: Page numbers for previous revisions may differ from page numbers in the current version.

| Version | Change Date | Change Item |
|---------|-------------|--|
| A.1 | 2021/02/05 | Initial version completed |
| A.2 | 2022/04/27 | 1. Added the TAPE AND REEL INFORMATION 2. Update PACKAGE MARKING on Page 5 in RevA.1 |
| A.2.1 | 2024/02/28 | Modify packaging naming |
| A.3 | 2024/04/29 | 1. Add MSL on Page 5 in RevA.2.1 2. Add Package thermal impedance on Page 4 in RevA.2.1 3. Add XDFN1X1-6 PACKAGE |
| A.4 | 2024/09/23 | 1. Update MSL NOTE 2. Update XDFN1X1-6 Pin1 Quadrant on Page 14 in RevA.3 3. Update V _{IL} PARAMETER 4. Update ESD Ratings 5. Update the description of ESD Ratings |


6 PACKAGE/ORDERING INFORMATION ⁽¹⁾

| PRODUCT | ORDERING NUMBER | TEMPERATURE RANGE | PACKAGE LEAD | PACKAGE MARKING ⁽²⁾ | MSL ⁽³⁾ | PACKAGE OPTION |
|---------|-----------------|-------------------|-----------------------|--------------------------------|--------------------|---------------------|
| RS1G126 | RS1G126XF5 | -40°C ~+125°C | SOT23-5 | 1G126 | MSL3 | Tape and Reel, 3000 |
| | RS1G126XC5 | -40°C ~+125°C | SC70-5 ⁽⁴⁾ | 1G126 | MSL3 | Tape and Reel, 3000 |
| | RS1G126XUTDN6 | -40°C ~+125°C | XDFN1X1-6 | 26 ⁽⁵⁾ | MSL3 | Tape and Reel, 5000 |

NOTE:

- (1) of this document. For browser-based versions of this data sheet, refer to the right-hand navigation.
- (2) There may be additional marking, which relates to the lot trace code information (data code and vendor code), the logo or the environmental category on the device.
- (3) Runic classify the MSL level with using the common preconditioning setting in our assembly factory conforming to the JEDEC industrial standard J-STD-20F, Please align with Runic if your end application is quite critical to the preconditioning setting or if you have special requirement.
- (4) Equivalent to SOT353.
- (5) 26: Identification Code.

7 PIN CONFIGURATIONS



PIN DESCRIPTION

| PIN | | NAME | I/O TYPE ⁽¹⁾ | FUNCTION |
|----------------|-----------|-----------------|-------------------------|-----------------|
| SOT23-5/SC70-5 | XDFN1X1-6 | | | |
| 1 | 1 | OE | I | OE Enable/Input |
| 2 | 2 | A | I | A Input |
| 3 | 3 | GND | - | Ground Pin |
| 4 | 4 | Y | O | Y Output |
| - | 5 | NC | - | Not connected |
| 5 | 6 | V _{cc} | - | Power Pin |

(1) I=input, O=output.

8 SPECIFICATIONS

8.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted) ^{(1) (2)}

| | | MIN | MAX | UNIT |
|------------------|---|-----------|----------------------|------|
| V _{CC} | Supply voltage range | -0.5 | 6.5 | V |
| V _I | Input voltage range ⁽²⁾ | -0.5 | 6.5 | V |
| V _O | Voltage range applied to any output in the high-impedance or power-off state ⁽²⁾ | -0.5 | 6.5 | V |
| V _O | Voltage range applied to any output in the high or low state ^{(2) (3)} | -0.5 | V _{CC} +0.5 | V |
| I _{IK} | Input clamp current | | -50 | mA |
| I _{OK} | Output clamp current | | -50 | mA |
| I _O | Continuous output current | | ±50 | mA |
| | Continuous current through V _{CC} or GND | | ±100 | mA |
| θ _{JA} | Package thermal impedance ⁽⁴⁾ | SOT23-5 | 230 | °C/W |
| | | SC70-5 | 380 | |
| | | XDFN1X1-6 | 438 | |
| T _J | Junction temperature ⁽⁵⁾ | -65 | 150 | °C |
| T _{stg} | Storage temperature | -65 | 150 | °C |

- (1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating Conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The input and output negative-voltage ratings may be exceeded if the input and output current ratings are observed.
- (3) The value of V_{CC} is provided in the Recommended Operating Conditions table.
- (4) The package thermal impedance is calculated in accordance with JESD-51.
- (5) The maximum power dissipation is a function of T_{J(MAX)}, R_{θJA}, and T_A. The maximum allowable power dissipation at any ambient temperature is P_D = (T_{J(MAX)} - T_A) / R_{θJA}. All numbers apply for packages soldered directly onto a PCB.

8.2 ESD Ratings

The following ESD information is provided for handling of ESD-sensitive devices in an ESD protected area only.

| | | VALUE | UNIT |
|--------------------|---|-------|------|
| V _(ESD) | Electrostatic discharge | | |
| | Human-body model (HBM), per EIA/JESD22-a114, all pins | ±4000 | V |
| | Charged-device model (CDM), per JS-002, all pins | ±1000 | V |
| | Machine model (MM), per EIA/JESD22-a115, all pins | ±200 | V |



ESD SENSITIVITY CAUTION

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

9 ELECTRICAL CHARACTERISTICS

over recommended operating free-air temperature range (TYP values are at $T_A = +25^\circ\text{C}$, unless otherwise noted.)⁽¹⁾

9.1 Recommended Operating Conditions

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | MAX | UNIT |
|-------------------------------|------------|--|----------------------|---------------------|------------------|
| Supply Voltage | V_{CC} | Operating | 1.65 | 5.5 | V |
| | | Data retention only | 1.5 | 5.5 | |
| High-Level Input Voltage | V_{IH} | $V_{CC}=1.65\text{V to }1.95\text{V}$ | $0.65 \times V_{CC}$ | | V |
| | | $V_{CC}=2.3\text{V to }2.7\text{V}$ | 1.7 | | |
| | | $V_{CC}=3\text{V to }3.6\text{V}$ | 2.2 | | |
| | | $V_{CC}=4.5\text{V to }5.5\text{V}$ | $0.7 \times V_{CC}$ | | |
| Low-Level Input Voltage | V_{IL} | $V_{CC}=1.65\text{V to }1.95\text{V}$ | | $0.3 \times V_{CC}$ | V |
| | | $V_{CC}=2.3\text{V to }2.7\text{V}$ | | 0.7 | |
| | | $V_{CC}=3\text{V to }3.6\text{V}$ | | 0.8 | |
| | | $V_{CC}=4.5\text{V to }5.5\text{V}$ | | $0.3 \times V_{CC}$ | |
| Input Voltage | V_I | | 0 | 5.5 | V |
| Output Voltage | V_O | | 0 | V_{CC} | V |
| Input Transition Rise or Fall | t_r, t_f | $V_{CC}=1.8\text{V} \pm 0.15\text{V}, 2.5\text{V} \pm 0.2\text{V}$ | | 20 | ns/V |
| | | $V_{CC}=3.3\text{V} \pm 0.3\text{V}$ | | 10 | |
| | | $V_{CC}=5\text{V} \pm 0.5\text{V}$ | | 5 | |
| Operating Temperature | T_A | | -40 | +125 | $^\circ\text{C}$ |

(1) All unused inputs of the device must be held at V_{CC} or GND to ensure proper device operation.

9.2 DC Characteristics

| PARAMETER | | TEST CONDITIONS | V _{CC} | TEMP | MIN ⁽²⁾ | TYP ⁽³⁾ | MAX ⁽²⁾ | UNIT |
|------------------|----------------|--|-----------------|-------|----------------------|--------------------|--------------------|------|
| V _{OH} | | I _{OH} = -100μA | 1.65V to 5.5V | Full | V _{CC} -0.1 | | | V |
| | | I _{OH} = -4mA | 1.65V | | 1.2 | | | |
| | | I _{OH} = -8mA | 2.3V | | 1.9 | | | |
| | | I _{OH} = -16mA | 3V | | 2.4 | | | |
| | | I _{OH} = -24mA | | | 2.3 | | | |
| | | I _{OH} = -32mA | 4.5V | | 3.8 | | | |
| V _{OL} | | I _{OL} = 100μA | 1.65V to 5.5V | Full | | | 0.1 | V |
| | | I _{OL} = 4mA | 1.65V | | | | 0.45 | |
| | | I _{OL} = 8mA | 2.3V | | | | 0.3 | |
| | | I _{OL} = 16mA | 3V | | | | 0.4 | |
| | | I _{OL} = 24mA | | | | | 0.55 | |
| | | I _{OL} = 32mA | 4.5V | | | | 0.55 | |
| I _I | A or OE inputs | V _I =5.5V or GND | 0V to 5.5V | +25°C | | ±0.1 | ±1 | μA |
| | | | | Full | | | ±5 | |
| I _{off} | | V _I or V _O =5.5V | 0V | +25°C | | ±0.1 | ±1 | μA |
| | | | | Full | | | ±10 | |
| I _{OZ} | | V _O =0V to 5.5V | 3.6V | Full | | | 10 | μA |
| I _{CC} | | V _I =5.5V or GND, I _O =0 | 1.65V to 5.5V | +25°C | | 0.1 | 1 | μA |
| | | | | Full | | | 10 | |
| ΔI _{CC} | | One input at V _{CC} -0.6V, Other inputs at V _{CC} or GND | 3V to 5.5V | Full | | | 500 | μA |

(1) All unused inputs of the device must be held at V_{CC} or GND to ensure proper device operation.

(2) Limits are 100% production tested at 25°C. Limits over the operating temperature range are ensured through correlations using statistical quality control (SQC) method.

(3) Typical values represent the most likely parametric norm as determined at the time of characterization. Actual typical values may vary over time and will also depend on the application and configuration.

9.3 Switching Characteristics, $C_L=15pF$

over recommended operating free-air temperature range (-40°C to 125°C, unless otherwise noted.)⁽¹⁾

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CC}=1.8V\pm0.15V$ | $V_{CC}=2.5V\pm0.2V$ | $V_{CC}=3.3V\pm0.3V$ | $V_{CC}=5V\pm0.5V$ | UNIT |
|-----------|--------------|-------------|-----------------------|----------------------|----------------------|--------------------|------|
| | | | TYP | TYP | TYP | TYP | |
| t_{pd} | A | Y | 6.1 | 3.7 | 3.9 | 2.1 | ns |

(1) All unused inputs of the device must be held at V_{CC} or GND to ensure proper device operation.

9.4 Switching Characteristics, $C_L=30pF$ or $50pF$

over recommended operating free-air temperature range (-40°C to 125°C, unless otherwise noted.)⁽¹⁾

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CC}=1.8V\pm0.15V$ | $V_{CC}=2.5V\pm0.2V$ | $V_{CC}=3.3V\pm0.3V$ | $V_{CC}=5V\pm0.5V$ | UNIT |
|-----------|--------------|-------------|-----------------------|----------------------|----------------------|--------------------|------|
| | | | TYP | TYP | TYP | TYP | |
| t_{pd} | A | Y | 8.6 | 5.3 | 4.0 | 2.9 | ns |
| t_{en} | OE | Y | 9.5 | 5.8 | 5.0 | 3.3 | ns |
| t_{dis} | OE | Y | 7.4 | 4.3 | 4.4 | 3.0 | ns |

(1) All unused inputs of the device must be held at V_{CC} or GND to ensure proper device operation.


9.5 Operating Characteristics

$T_A=25^\circ C$

| PARAMETER | | | TEST CONDITIONS | $V_{CC}=1.8V$ | $V_{CC}=2.5V$ | $V_{CC}=3.3V$ | $V_{CC}=5V$ | UNIT |
|-----------|-------------------------------|-----------------|-----------------|---------------|---------------|---------------|-------------|------|
| | | | | TYP | TYP | TYP | TYP | |
| C_{pd} | Power Dissipation Capacitance | Output Enabled | f=10MHz | 18 | 18 | 19 | 21 | pF |
| | | Output Disabled | | 2 | 2 | 2 | 4 | |


(1) All unused inputs of the device must be held at V_{CC} or GND to ensure proper device operation.

10 PARAMETER MEASUREMENT INFORMATION



| TEST | S1 |
|-------------------|------------|
| t_{PLH}/t_{PHL} | Open |
| t_{PLZ}/t_{PZL} | V_{LOAD} |
| t_{PHZ}/t_{PZH} | GND |

| V_{CC} | INPUTS | | V_M | V_{LOAD} | C _L | | R _L | | V_{Δ} |
|------------|----------|-----------|------------|--------------|----------------|------|----------------|------|--------------|
| | V_I | t_r/t_f | | | | | | | |
| 1.8V±0.15V | V_{CC} | ≤2ns | $V_{CC}/2$ | 2 x V_{CC} | 15pF | 30pF | 1MΩ | 1kΩ | 0.15V |
| 2.5V±0.2V | V_{CC} | ≤2ns | $V_{CC}/2$ | 2 x V_{CC} | 15pF | 30pF | 1MΩ | 500Ω | 0.15V |
| 3.3V±0.3V | 3V | ≤2.5ns | 1.5V | 6V | 15pF | 50pF | 1MΩ | 500Ω | 0.3V |
| 5V±0.5V | V_{CC} | ≤2.5ns | $V_{CC}/2$ | 2 x V_{CC} | 15pF | 50pF | 1MΩ | 500Ω | 0.3V |







- NOTES:
- A. C_L includes probe and jig capacitance.
 - B. Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
 - C. All input pulses are supplied by generators having the following characteristics: PRR ≤ 10 MHz, Z_o = 50 Ω.
 - D. The outputs are measured one at a time, with one transition per measurement.
 - E. t_{PLZ} and t_{PHZ} are the same as t_{dis} .
 - F. t_{PZL} and t_{PZH} are the same as t_{en} .
 - G. t_{PLH} and t_{PHL} are the same as t_{pd} .
 - H. All parameters and waveforms are not applicable to all devices.

Figure 1. Load Circuit and Voltage Waveforms

11 PACKAGE OUTLINE DIMENSIONS





SOT23-5⁽³⁾


RECOMMENDED LAND PATTERN (Unit: mm)


| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|------------------|---------------------------|-------|---------------------------|-------|
| | Min | Max | Min | Max |
| A ⁽¹⁾ | 1.050 | 1.250 | 0.041 | 0.049 |
| A1 | 0.000 | 0.100 | 0.000 | 0.004 |
| A2 | 1.050 | 1.150 | 0.041 | 0.045 |
| b | 0.300 | 0.500 | 0.012 | 0.020 |
| c | 0.100 | 0.200 | 0.004 | 0.008 |
| D ⁽¹⁾ | 2.820 | 3.020 | 0.111 | 0.119 |
| E ⁽¹⁾ | 1.500 | 1.700 | 0.059 | 0.067 |
| E1 | 2.650 | 2.950 | 0.104 | 0.116 |
| e | 0.950(BSC) ⁽²⁾ | | 0.037(BSC) ⁽²⁾ | |
| e1 | 1.800 | 2.000 | 0.071 | 0.079 |
| L | 0.300 | 0.600 | 0.012 | 0.024 |
| θ | 0° | 8° | 0° | 8° |

NOTE:






1. Plastic or metal protrusions of 0.15mm maximum per side are not included.
2. BSC (Basic Spacing between Centers), "Basic" spacing is nominal.
3. This drawing is subject to change without notice.

SC70-5 (3)

RECOMMENDED LAND PATTERN (Unit: mm)


| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|------------------|---------------------------|-------|---------------------------|-------|
| | Min | Max | Min | Max |
| A ⁽¹⁾ | 0.900 | 1.100 | 0.035 | 0.043 |
| A1 | 0.000 | 0.100 | 0.000 | 0.004 |
| A2 | 0.900 | 1.000 | 0.035 | 0.039 |
| b | 0.150 | 0.350 | 0.006 | 0.014 |
| c | 0.080 | 0.150 | 0.003 | 0.006 |
| D ⁽¹⁾ | 2.000 | 2.200 | 0.079 | 0.087 |
| E ⁽¹⁾ | 1.150 | 1.350 | 0.045 | 0.053 |
| E1 | 2.150 | 2.450 | 0.085 | 0.096 |
| e | 0.650(BSC) ⁽²⁾ | | 0.026(BSC) ⁽²⁾ | |
| e1 | 1.300(BSC) ⁽²⁾ | | 0.051(BSC) ⁽²⁾ | |
| L | 0.260 | 0.460 | 0.010 | 0.018 |
| L1 | 0.525 | | 0.021 | |
| θ | 0° | 8° | 0° | 8° |

NOTE:

1. Plastic or metal protrusions of 0.15mm maximum per side are not included.
2. BSC (Basic Spacing between Centers), "Basic" spacing is nominal.
3. This drawing is subject to change without notice.

XDFN1X1-6⁽³⁾

TOP VIEW

LAND PATTERN EXAMPLE

SIDE VIEW

SIDE VIEW

BOTTOM VIEW


| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|------------------|----------------------------|-------|----------------------------|-------|
| | Min | Max | Min | Max |
| A ⁽¹⁾ | 0.340 | 0.400 | 0.013 | 0.016 |
| A1 | 0.000 | 0.050 | 0.000 | 0.002 |
| A3 | 0.100 (REF) ⁽²⁾ | | 0.004 (REF) ⁽²⁾ | |
| b | 0.100 | 0.200 | 0.004 | 0.008 |
| D ⁽¹⁾ | 0.950 | 1.050 | 0.037 | 0.041 |
| E ⁽¹⁾ | 0.950 | 1.050 | 0.037 | 0.041 |
| e | 0.300 | 0.400 | 0.012 | 0.016 |
| H | 0.100 (REF) ⁽²⁾ | | 0.004 (REF) ⁽²⁾ | |
| K | 0.150 | | 0.006 | |
| L | 0.350 | 0.450 | 0.014 | 0.018 |
| L1 | 0.350 | 0.450 | 0.014 | 0.018 |
| L2 | 0.075 (REF) ⁽²⁾ | | 0.003 (REF) ⁽²⁾ | |

NOTE:


1. Plastic or metal protrusions of 0.075mm maximum per side are not included.
2. REF is the abbreviation for Reference.
3. This drawing is subject to change without notice.

12 TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSION



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF TAPE AND REEL

| Package Type | Reel Diameter | Reel Width (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P0 (mm) | P1 (mm) | P2 (mm) | W (mm) | Pin1 Quadrant |
|--------------|---------------|-----------------|---------|---------|---------|---------|---------|---------|--------|---------------|
| SC70-5 | 7" | 9.5 | 2.25 | 2.55 | 1.20 | 4.0 | 4.0 | 2.0 | 8.0 | Q3 |
| SOT23-5 | 7" | 9.5 | 3.20 | 3.20 | 1.40 | 4.0 | 4.0 | 2.0 | 8.0 | Q3 |
| XDFN1X1-6 | 7" | 9.5 | 1.14 | 1.17 | 0.56 | 4.0 | 4.0 | 2.0 | 8.0 | Q3 |

NOTE:

1. All dimensions are nominal.
2. Plastic or metal protrusions of 0.15mm maximum per side are not included.

IMPORTANT NOTICE AND DISCLAIMER

Jiangsu Runic Technology Co., Ltd. will accurately and reliably provide technical and reliability data (including data sheets), design resources (including reference designs), application or other design advice, WEB tools, safety information and other resources, without warranty of any defect, and will not make any express or implied warranty, including but not limited to the warranty of merchantability Implied warranty that it is suitable for a specific purpose or does not infringe the intellectual property rights of any third party.

These resources are intended for skilled developers designing with Runic products You will be solely responsible for: (1) Selecting the appropriate products for your application; (2) Designing, validating and testing your application; (3) Ensuring your application meets applicable standards and any other safety, security or other requirements; (4) Runic and the Runic logo are registered trademarks of Runic Incorporated. All trademarks are the property of their respective owners; (5) For change details, review the revision history included in any revised document. The resources are subject to change without notice. Our company will not be liable for the use of this product and the infringement of patents or third-party intellectual property rights due to its use.